


>163,65546 67818,7-23987 911 56-203 88849<  
>198,65546 65612,23-2829 955 56-203 46549<  
>198,65546 65612,23-2829 95556-203 46549<  
>152,698016 68818,23-2399 92356-203 85549<  
>198,643636 78617,73-2289 783 56-203 55549<  
>124,634546 78672,23-7779 683 56-203 88349<  
>458,11142 83417,73-2397 876 56-203 83339<  
>145,523286 64486,22-2689 986 56-203 88849<  
>368,688789 12437,23-2333 977 56-203 55549<



**DATA SHEET**

**MODEL 6242T**

**Automated Secondary Thermometry Bridge**



- **0.1 to 10,000 Ohm Range**
- **Best Accuracy: < 0.1 PPM (0.025m°C)**
- **Maximum Ratio: 14:1**
- **DC Current Comparator Technology**
- **Resolution: 0.01 PPM**
- **Linearity: 0.01 PPM**

**MODEL INFORMATION**

The Model 6242T is a high accuracy resistance bridge designed specifically for resistance thermometry. Based on the Direct Current Comparator, its unique DC Reversal eliminates thermal EMF effects to provide you with fast, reliable measurements under a wide range of real operating conditions. Four terminal measurements allow you to make measurements up to 100 meters and more from the PRT. The differential capability allows the resistance of one PRT to be measured against another directly and provides the most accurate comparison calibration technique.

The Model 6242T Automated Secondary Temperature Bridge is ideal for those laboratories involved in resistance and temperature measurements that do not require the accuracy level of an NMI. It is also designed as an automated, direct replacement for the ASL F700 Temperature measurement system. The 6242T is based on the same Direct Current Comparator technology found in the bridge used by major laboratories to maintain their primary standards, the Model 6010. Therefore, it has some of the same features that metrologists have come to expect in an MIL bridge, such as four terminal measurements over the complete range, automatic current reversal to

eliminate thermal EMF's and a built-in self-calibration routine.


The 6242T features include a front panel display, standard IEEE488 interface and two input channels. Up to three PRTs can be entered via the front panel keys. Besides temperature, the 6242T is capable of measuring resistance and resistance ratio. All uncertainties are calculated to 2 sigma.

An optional, easy to use Windows® based software package is also available. It offers the features that metrologists expect such as the ability to perform automatic data acquisition, real time uncertainty analysis, graphing, history logging and regression analysis.

The 6242T can be used with one or more of MIL 4200 series of scanners for multi channel calibration.



>163,65546 67818,7-23987 911 56-203 88889<  
 >198,65546 65612,23-2829 955 56-203 46549<  
 >198,65546 65612,23-2829 95556-203 46549<  
 >152,698016 68818,28-2399 92356-203 85549<  
 >198,643636 78617,73-2289 783 56-203 55549<  
 >124,634546 78672,23-7779 683 56-203 88349<  
 >458,11142 83417,73-2397 876 56-203 83339<  
 >145,523286 64486,22-2689 986 56-203 88849<  
 >368,688789 12437,23-2333 977 56-203 55549<



**Specifications:**

Resistance Range	Accuracy (PPM)
1 to 10,000 Ω	< 0.1 (0.025 m°C)
0.1 to 1 Ω	< 0.5 (0.1 m°C)
Voltage Noise	< 10 nV
Thermometers	R 1000 Ω, 100Ω, 25Ω, 10Ω, 1Ω or any Intermediate value
Measurement range	0 to 14 where Rs = 0.1, 1, 10, 100 Ω
External Standards	0.1 Ω to 1000 Ω
Linearity	±0.01 PPM
Input Channels	2 (expandable to 40), Tellurium Copper - Rear Panel
Test Current Range	20μ to 100m Amps FS
√2 @ 1/√2	Front Panel Selectable on any current
Current Resolution	16 bit
Current Reversal	2 to 1000 Seconds
Time to Stated Accuracy (warm-up)	<20 sec.
Measurement Time	<20 sec.
Temperature Co-efficient	±0.01 PPM/°C
Resolution	± 0.01 PPM of full scale
Mode of Operation	Manual or Automatic (IEEE488)
Operating Conditions	0 to 34°C, 10 to 90% RH
Operating Power (Selectable)	100, 120, 220, 240V - 50/60Hz
Warranty	2 Year Parts & Labor

**Weight:**  
 17 kg (35 lb.)

**Dimensions:**  
 H 179mm (7 in) x W 484 mm (19 in) x L 484 mm (19 in)

**Accessories Included:**  
 6242T Software for W98/2000/XP/Vista  
 IEEE 488 Card & Cable  
 One 9331 Standard Resistor (Specified Value)  
 SPSCW XX YY 4 (4 conductor cable)

**Optional Accessories:**  
 4220A Low Thermal Matrix Scanner  
 612.5 mm (24 inch) high Equipment Rack  
 9331 Standard Resistors (1, 10, 25, 100, 1kΩ)

**Distributed By:**

**How to Order:**  
 Model 6242T Automated Secondary Thermometry  
 Bridge

Form MI 66, Rev. 5, Dated 08-08-18 (QAP19, App. "N")

Data Subject to Change-Revision 2

**MI-Canada**

Measurements International Ltd.  
 PO Box 5934, 118 Commerce Drive  
 Prescott, Ontario, Canada K0E 1T0

Phone: (613) 925-5934  
 Fax: (613) 925-1195

Email: sales@mintl.com

**MI-USA**

Measurements International Inc  
 815 Eyrie Dr. Suite #4  
 Oviedo, FL 32765

Toll Free: 1-800-324-4988  
 Phone: (407) 706-0328  
 Fax: (407) 706-0318

Email: sales@mintl.com

**MI-Europe**

Druzstevni 845  
 686 05 Uherske Hradiste  
 Czech Republic

Phone: (420) 572-572-801  
 Fax: (420) 572-572 358

Email: sales@mintl.com

www.mintl.com

